

REC'D 20 FEB 2004
WIPO PCT

PL 1129067

THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office

February 13, 2004


THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM
THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK
OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT
APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A
FILING DATE.

APPLICATION NUMBER: 60/425,382

FILING DATE: November 12, 2002

RELATED PCT APPLICATION NUMBER: PCT/US03/36320

By Authority of the
COMMISSIONER OF PATENTS AND TRADEMARKS



A handwritten signature in black ink, appearing to read "P. Swain".

P. SWAIN
Certifying Officer

PRIORITY DOCUMENT
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH
RULE 17.1(a) OR (b)

11/12/02
JC944 U.S. PTO

Please type a plus sign (+) inside this box

11 - 18 - 10 2002 REQUESTED BY [REDACTED] 11/12/02/prov

PTO/SB/16 (02-01)

Approved for use through 10/31/2002. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53 (c).

Express Mail Label No. EV 104020493 US

INVENTOR(S)

Given Name (first and middle [if any])	Family Name or Surname	Residence (City and either State or Foreign Country)
KEITH ROBERT	BROERMAN	CARMEL, INDIANA
GLEN WAKEMAN	RUCH	INDIANAPOLIS, INDIANA
BLAINE EDWARD	RAMEY	INDIANAPOLIS, INDIANA
BRIAN DAVID	BAEHL	NOBLESVILLE, INDIANA

Additional inventors are being named on the _____ separately numbered sheets attached hereto


TITLE OF THE INVENTION (280 characters max)

METHOD AND APPARATUS FOR GENERATING AND PLAYING DIAGNOSTIC MESSAGES INDICATIVE OF MTA
PROVISIONING STATUS

CORRESPONDENCE ADDRESS

Direct all correspondence to:

Customer Number



Place Customer Number
Bar Code Label here

OR

Type Customer Number here

Firm or
Individual Name

JOSEPH S. TRIPOLI, THOMSON MULTIMEDIA LICENSING INC.

Address

PATENT OPERATIONS.

Address

P. O. BOX 5312

City

PRINCETON

State

NJ

ZIP

08543-5312

Country

USA

Telephone

609-734-9444

Fax

609-734-9700

ENCLOSED APPLICATION PARTS (check all that apply)

Specification Number of Pages

3

CD(s), Number

Drawing(s) Number of Sheets

Other (specify)

Application Data Sheet. See 37 CFR 1.76

METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT (check one)

Applicant claims small entity status. See 37 CFR 1.27.

A check or money order is enclosed to cover the filing fees

FILING FEE
AMOUNT (\$)

The Commissioner is hereby authorized to charge filing
fees or credit any overpayment to Deposit Account Number:

07-0832

160

Payment by credit card. Form PTO-2038 is attached.

The invention was made by an agency of the United States Government or under a contract with an agency of
the United States Government.

No.

Yes, the name of the U.S. Government agency and the Government contract number are: _____

Respectfully submitted,

SIGNATURE

Date

11/12/02

TYPED or PRINTED NAME

PAUL P. KIEL

REGISTRATION NO.

40,677

(if appropriate)

Docket Number:

PU020453

TELEPHONE 609 734 6815

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is used by the public to file (and by the PTO to process) a provisional application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 6 hours to complete, including gathering, preparing, and submitting.

JC857 U.S. PTO
60/425382

BEST AVAILABLE COPY

Exp. mail: EV 104020493 US

PU020453

METHOD AND APPARATUS FOR GENERATING AND PLAYING DIAGNOSTIC MESSAGES INDICATIVE OF MTA PROVISIONING STATUS

In accordance with the present invention, if a phone is taken off-hook on an MTA that is not provisioned, improperly provisioned, or placed in an out-of-order state by the MSO, the MTA will generate an appropriate diagnostic audio voice message or tone sequence to the telephone instructing the listener on how to proceed in order to resolve the problem.

Background of the Invention

Media terminal adaptors (MTAs) require a strict provisioning sequence prior to becoming operational. In a PacketCable environment a total of 25 steps must be completed to become operational, and 11 additional steps must be completed in order to establish IPSec security associations with the call agent. These provisioning steps are controlled by the MSO and are a function of the MSO Provisioning Server (MTA DHCP options & MTA configuration file), the MSO's DNS configuration, and the configuration of the MSO call agent and Kerberos Key Distribution Center (KDC.) Failure to properly configure any of these items can leave the MTA in a non-provisioned or improperly configured state which will render the MTA nonfunctional or out-of-order. In this context, out-of-order means that dial tone is not heard on the handset when the phone attached to the MTA is taken off-hook.

Description of the Invention

This invention provides several methods to indicate to the user that the MTA has not been properly configured and that the user should contact their service provider to resolve the issue. These methods involve playing an audio sequence consisting of a voice message and/or a sequence of audio tones to indicate the specific problem and what to do to resolve the issue.

Existing cable modems and MTAs, use discrete LEDs or a 7-segment LED display to indicate provisioning status and possibly, the first provisioning step that has failed. Due to the small number of product LEDs (typically 5 to 6, or one 7-segment display) and large number of provisioning steps it is difficult to indicate the precise cause of a provisioning failure. Approaches have been used to display the provisioning status via blinking LEDs, displaying the status code in a binary format, etc. Many non-technical consumers are not able to easily correlate the blinking LED codes with a table in the user manual in order to resolve their specific problem.

In this invention, the MTA generates an audible diagnostic message to the user, over the attached telephone(s), indicating:

1. the presence of a provisioning error
2. the nature of the error (which provisioning step failed)
3. what step should be taken to resolve the error.

In this invention, the audible message can consist of either a voice message or a sequence of audio tones, or both. The voice message and/or audio tone sequence can be either

Exp. mail: EV 104020493 US

PU020453

canned (fixed, stored in local non-volatile memory) or dynamically generated. The audio clip could combine fixed voice text with dynamically-generated voice text such as a specific telephone number to dial. The variable information used to generate the dynamic portion of the message could be stored in non-volatile memory or passed to the MTA via a proprietary configuration file TLV or MIB element. In this way the diagnostic message can be tailored for a specific service provider, location, etc.

In addition to or alternatively, a sequence of audio tones (including a 'beep' sequence or a series of DTMF tones) could be played to convey the diagnostic message. DTMF tones would be suitable for machine recognition, by, for example, test equipment used by a field technician.

In addition to or alternatively, the telephone handset keypad can be used to request additional diagnostic or status information. An audible message can prompt the listener to enter one or more keypad digits in order to retrieve more detailed status information. The information would not be limited to diagnostics, and could include MTA operating status such as current upstream and downstream frequency, power level, and signal to noise ratio.

In this invention, the MTA's DSP (digital signal processor) and POTS (plain old telephone service) endpoint circuitry is enabled early in the boot-up sequence, prior to the start of device provisioning. If MTA provisioning is successful, the MTA enters its normal operating mode and the user hears dial tone when he takes a phone off-hook. If MTA provisioning was not successful or if the service provider placed the MTA in an out-of-order state via MTA configuration file or MTA MIB element settings, the MTA will play an appropriate diagnostic audio message (voice and/or tone sequence) when the user takes the phone off-hook. The MTA software will generate audio messages by encapsulating the audio in an RTP (real time protocol, RFC-1889/1890) packet stream to emulate the reception of said data from the network. This audio stream, consisting of an ordered sequence of near-synchronous RTP packets, is sent to the MTA DSP and endpoint circuitry. As with audio packets received from the network, the DSP de-packetizes the RTP audio data and places it in its outbound jitter buffer for use by the speech decoder circuit. The speech decoder converts the digital PCM audio data to analog samples which are reconstructed in the endpoint circuitry and played to the listener. The existing endpoint circuitry and control software monitors the telephone hook state and generates the diagnostic audio message when an off-hook condition is detected.

As an example, the following audio messages could be played under the following provisioning error conditions:

Unable to obtain IP address

"Your MTA cannot obtain a network address. Please contact XYZ Cable Company at 317-587-3168." Thank you."

Missing DHCP options

"Your MTA requires one or more missing DHCP options. Please contact XYZ Cable Company at 317-587-3168." Thank you."

CONFIDENTIAL - M/S/ET/EE

Exp. mail: EV 104020493 US

, PU020453

MTA is provisioned but not enabled

"Your MTA has been administratively disabled. Please contact XYZ Cable Company at 317-587-3168." Thank you."

BEST AVAILABLE COPY